Certificate of Location of Government Corner

ID#: 603005 **Description:** W SEC COR 30 31 60 **Date Set:** 7/24/1980 **County:** Winona

Section: 30 **Township:** 106N **Range:** 10W **Monument Description:** Winona County Monument

Reference Ties:

The corner falls 6' south of centerline of CSAH 29
County Survey Disk in E side PP SE 50.83'
Punch mark in W end 15" CMP N 24.31'
Winona Co. reference iron S 71.62'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: N. 80.00 chains set post corner. BT's - Burr Oak S79°W 18 links, Burr Oak N42°W 54 links, Burr Oak S30°E 50", Burr Oak N15°E 119 links.

1943 county highway department (B.180 P.76) A. Armstrong dug extensively all across road in line fences N-S, found old post remains at east 1/4 36. Set corner east 25-36 a 1/2" rod midway NE 25 and SE 36'. Meas each mile 5267.1 on line N-S fences only. Meas south to corner post remains E 1/4 36 2634.8. Meas north to corner post remains E 1/4 25 2635.7. RP's - E 25-36 F cor S 23.6' F cor N 33.3', disc in 10" apple SW 67.87', disc PP #1 up 4'. Later RP's - Disc in TP NW 32.65' ESE 86.82, disc in FP SW 37.35' PI about 50' from co. line? Meas west 2643.25' then 2638.95.

11-1961 Minn Hwy Dept. DuVal also Co. Hwy Dept., spike over boulder in centerline E-W road. MHD disc tele pole NW 44.45, MHD disc cor F.P. S 32.09, MHD power pole SE 89.84'

7-23-1980 Olmsted County Surveyor dug in Co. Rd. 29 and found 2 hubs (1) 2x2 hub and tack (2) 1x2 hub. The 2x2 hub fell in centerline of road. Dug again and found A. Armstrongs 5/8" rod 15" deep and 5.5' south centerline of E-W road. This point is 5.46' south and 0.46' west of the 2x2 hub found. Drove a 5/8" rod at the surface and took references. RP's - CS disc in power pole (E side) SE 50.83'. Punch mark in west end 15" field drive culvert north 24.31'.

6-1984 Tom Ferguson survey in sec. 30-106-10. Found (dip?) in road ± 5.5' south of centerline apparently did not dig up County Surveyor 1980 iron.

3-1989 Winona County Highway Dept. found 5/8" rod by Olmsted County Surveyor 5 1/2' south of centerline.

5-18-1995 Winona County Surveyor took reference ties to 5/8" iron.

7-22-2003 Olmsted County Surveyor found Winona County Monument at surface in good condition.