Certificate of Location of Government Corner

ID#: 603006 **Description:** W 1/4 SEC COR 30 60 **Date Set:** 6/18/1984 **County:** Winona

Section: 30 **Township:** 106N **Range:** 10W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fences east and south and 7' SSW of CP
State Reference Point in SW side 22" Burr Oak SE 13.97'
County Survey Disk in E side 20" Burr Oak NNE 60.10'
Center 21" Burr Oak NE 66.6'
State Reference Point in NW side CP NNE 5.97'
The corner is located by GPS reference stations "Milkshake A & B"

Corner History:

1853 Gov't Notes: North 40.00 chains set quarter section post. BT's - White Oak N 55°W 49 links = 32.34'. Burr Oak S82°E 66 links = 43.56'. Creek 3 links wide runs NW, north 5 chains.

No records. Minn Hwy. Dept. assumed point from RP's wash out.

1960 MHD 3/4" rod to SE cor 25. MHD disc cor fence post NW 3.65. MHD disc 18" oak SE 11.7. MHD disc 18" oak S 13.15. Archie's notes B.180 P.76 say 2635.7 to SE 25?

1943 county highway department Field book 180 P.76-78 by C.A. Armstrong. Survey was to set corner at east sec cor 25-36. Found Twp cor stone monu. top broken off at E 24-25 split dist (5267.1-5267.1) to set sec cor E 25-36 and in line of fences N & S at E 1/4 cor 25 (A3) found an old rotten stake or fence post but in line with fence running east and about 1' east of N-S fence meas 2631.4 N (apparently nothing else set to identify cor) 2635.7 S

3-1966 See cert of corner location by J. Kleinschmidt. Method of setting corner unknown.

6-1984 Tom Ferguson, survey in sec 30-106-10 found 3/4" rod set by Mn/Dot ± 4' E and 2' south of the corner post in place. Also found Kleinschmidt's pipe which is about 20' west and 2' south of corner post leaving about 24' between the 2, found irons.

6-18-1984 County Surveyor set CIM over 1/2" iron rod as 1/4 corner. Used line of E-W fence at a point ± 190' east and E 1/4 cor stone as per Tom Ferguson survey. Used line of NE 25 over a large ctnwd tree at 1/16 south of NE 25 and also line of C.A. Armstrong corner location at SE 25 over a post (old corner post of fences N-S and East) at the 1/16th location north of SE 25. These two lines produced to this 1/4 corner came about 2' apart, we split the 2' and set the CIM at a split for E-W location. CIM set is about 6.5' west and 3.2' south of the Mn/Dot 3/4" iron rod which we now removed. Also we are 17.53' easterly from Kleinschmidt's pipe which remains in place. Dug small hole 3' E-W x 4' N-S centering over location of set CIM. Dug down to yellow soil.

4-24-2003 County Surveyor found CIM in good condition SSW of corner post to fences East and South.