Certificate of Location of Government Corner

ID#: 603105 **Description:** SW SEC COR 31 60 **Date Set:** 10/26/2011 **County:** Winona

Section: 31 **Township:** 106N **Range:** 10W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is at the surface.
The corner falls 2' east of fence south and 2 1/2' north of E-W fence
Post w/sign 2' south
This corner is located by GPS reference stations "RDJ II & Lundeen II"

Corner History:

6-1853 Gov't Notes N 80.00 chains from S set post corner. B.T's - Burr Oak S45°E 28 links, Burr Oak N18-1/2W 36-1/2 links, Burr Oak N4-1/2°E 52 links, Burr Oak S70°W 36 links.

1875 State law required that monuments be set at township corners. Thomas Hunter, County Surveyor, placed stone monuments as required although there is no survey notes documenting this particular corner

4-1891 Thos Fraser (P.476 No.455 S.1) M. Hays found engraved township corner stone.

5-1900 Robert Fraser (P.674 No.599 S.1) F. Cornwell, J. Hayes found engraved township corner set by Hunter. 1/16 south drove stake M&L 20.02 for line west. Set stake at center NE 1/4 section 1.

9-2-1975 Olmsted County Surveyor found township monument at edge of cultivated field and just NE of large oak tree as corner to fences E-W-S set 1/2" rods on E and W sides. Corner 2' E of fence S and 2.5' N of E-W fence. RP's - spike and CSD NW side large Burr Oak SW 303.

7-21-1998 Olmsted County Surveyor found township monument (engraved stone).

6-25-2010 Olmsted County Survey Crew found 10x10x30 engraved cut stone monument with SE corner broke off leaning WNW up 0.1'. Shot leaning position with GPS and removed.

10-26-2011 Olmsted County survey crew set a 5' telspar pipe with cast iron cap at the coordinate location from 6-25-2010.