Certificate of Location of Government Corner

ID#: 610405 **Description:** SEC COR 4 5 8 9 61 **Date Set:** 10/20/1983 **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' north of centerline of E-W twp road and in line with fence south
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 8 and 9. 80.00 chs. Set post to corner to Sections 4,5,8,9. Made mound, trench, and pits and planted Cherry seed SE & SW, NE & NW.

6-1900 Robert Fraser, Deputy County Surveyor, (Book A, Page 687, No. 610) "Found corner post of fence with stones around which Mr. Betry claimed and others was the right corner. On record as glass under post." He used the corner to set the 1/16 West, a boulder stone and stake, midway (19.94 & 3/4 chs.) and on line to ¼ Cor. 5-8, a cottonwood tree claimed at corner location. He also used the corner to set ¼ Cor. 8-9, a Burr Oak stake with little stone beside, midway (40.175 chs.) and apparently on line to Sec. Cor. 8-9-16-17.

10-20-1983 County Surveyor set a Cast Iron Monument over a ½" re-rod as the corner at the location of the post mark found on the north side of the cedar post stub. Measured south 2649.12 to ¼ Cor. 8-9 (stake found in 1973) which is just .8' East and 1.0' North of midway and on line to Sec. Cor. 8-9-16-17 by electronic traverse computation.

7-29-2008 County Surveyor found CIM down 0.3' in good condition.