Certificate of Location of Government Corner

ID#: 610504 **Description:** 1/4 SEC COR 5 8 61 **Date Set:** 6/25/1995 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7'
The corner falls 2' south of centerline of E-W twp road and 3' west of fence south
County Survey Disk in PP #936 SW 33.59'
This corner is located by GPS measurement.

Corner History:

10-1853 Gov't Notes, John Ball, Deputy Surveyor West on true line between sections 5 and 8 40.03 chs. Set post at quarter section corner deposited handful of charcoal, made mound trench and pits, planted cherry seeds NE and SW.

6-1900 Robert Fraser, Deputy County Surveyor (Pg. 686, No. 610) Found Cottonwood tree claimed by old settler as planted in place of stake. Fence west and south, chained west 40.22½ chs. Set sixteenth corner east midway and online 19.94¾ chs. boulder and stake.

10-22-92 County Surveyor dug with backhoe in township road, found ±40" diameter Cottonwood stump, 2' deep, cut off and filled over with much woven wire circling stump. Drove ½" x 36" rod through center of stump.

6-26-1995 County Surveyor set CIM at position of Cottonwood stump found in 1992.

8-20-2010 County survey crew found CIM in good condition.