Certificate of Location of Government Corner

ID#: 610505 **Description:** SEC COR 5 6 7 8 61 **Date Set:** 9/12/1973 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.5' in centerline of CR132 and 4' south of twp road east
Conc. nail in W side PP #922 NNE 163.4'
Punch hole in N end CMP NE 31.0'
Bottle cap in S side PP #923 WSW 32.9'
Punch hole in S end CMP SE 28.95'
The corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 7 and 8. 80.00 chs. Set section corner post. Made mound, pits, trench, and planted cherry seeds. Deposited handful of charcoal.

5&8-1887 Thomas Hunter (P. 419 No. 408), County Surveyor, found quarry stone in center of the road, undesputed and claimed by settlers as true corner.

6-1900 Robert Fraser (P. 686 No. 610), County Surveyor, found stone 4"x6"x18".

1939 County Highway Dept. (Book 101 P. 76) found 5"x7"x18" stone. Placed 2"x2" hub in place of old stake found by stone.

9-12-1973 Roger Brand, County Surveyor, Found recorded stone 6' deep with wood hubs. Set irons on east and west sides with long twisted iron riser below C.I.M.

4-13-79 County Surveyor found C.I.M. in good condition.

8-20-2010 County survey crew found CIM in good condition