Certificate of Location of Government Corner

ID#: 610604 **Description:** 1/4 SEC COR 6 7 61 **Date Set:** 10/24/2011 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 11W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is down 1.1'

Corner History:

1853 Gov't Notes: J. Ball, set 1/4 corner section post 40 chs west of 5-6-7-8. Meas of mile 79.88 5272.08 meas west 2632.08.

5&8-1887 Hunter (P.419 No.408 S.6) J. Ketchum, W. Miller, corner in open field obliterated run line and meas see line 79.88 chs exactly gov't record. Set point 20 chs west SE cor 6 39.88 east SW cor 6. 1/16 east set stone 20.00 M&L 1320.0. 1/16 north set stake M&L 20.01 1320.66. 16 center SE 1/4 6 set stake and stone M&L 20.02 1321.32 on E-W 1/16 line.

4-1979 County Surveyor established computed corner location with no monument set (see drawing 4-35). The location was computed at the intersection of a line from the north quarter corner of section 6 through an iron rod at the center of section 6 with a line from the southeast corner of section 6 to the southwest corner of section 6.

10-24-2011 County survey crew set 4' telspar pipe with cast iron cap from 1979 computed coordinates