Certificate of Location of Government Corner

ID#: 610605 **Description:** W SEC COR 6 7 61 **Date Set:** 9/18/1973 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 10 1/2' west of centerline of N-S twp road and in centerline of twp road west
20d spike near No. plate #122 in S side PP SE 66.1'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor North between sections 7 and 12. 77.00 chs. Brook 4 lks. wide running N.E. 80.00 chs. Made mound with charred stake as corner. Dug trench and planted osage orange seed S.E. and apple seed N.E.

6-1875 Thomas Hunter (P. 281 No. 278), County Surveyor, found remains of old stake in mound by side of fence post. Marked post as witness corner.

10-1877 T. Hunter (caption on survey No. 281) set stone 2"x8"x16" as corner.

5-1887 T. Hunter (P. 419 No. 408) found stone set P. 281 caption.

9-18-1973 County Surveyor dug with tractor and found 2"x8" topped limestone down 2.5' deep. Set C.I.M. over stone found and set irons on east and west sides of stone.

6-13-2002 County Surveyor found CIM down 0.4' in good condition.

4-5-2007 County Surveyor found CIM down 0.4' in good condition.