Certificate of Location of Government Corner

ID#: 610805 **Description:** SEC COR 7 8 17 18 61 **Date Set:** 6/11/1974 **County:** Olmsted

Section: 08 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 10' west of centerline of CR 132, in centerline of twp road west and 2' north of fence east
Bottle cap in SW side PP #45 NW 52.15'
Punch hole in top N end 30" CMP NW 36.57'
Concrete nail in N side PP #46 E 76.15'
Punch hole in top S end 30" CMP SW 33.17'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes North between sections 17 and 18 80.00 chs Set section corner post Made mound, pits and trench, and planted cherry seed.

1890 Thomas Fraser, County Surveyor, could not find corner.

6-1900 Robert Fraser (P. 686 No. 610), County Surveyor, dug extensively but corner gone. Ran from N.W. Cor. 8 South to S.W. Cor. 17 and from S.E. Cor. 8 to S.W. Cor. 7 and set a 2" X 9" X 18" limestone and boulder by side of dry burr oak stake as corner by double proportionate measure.

9-17-1973 County Surveyor dug with tractor and found a 4" diameter very solid wood stake 4' down with long limestone on east side and large boulders on west and south sides and a small boulder over stake. Set 5/8" x 3' rod riser with 120d nail in top of wood stake.

6-11-1974 County Surveyor reset C.I.M. over 1/2" x 3' rod.

3-21-2007 County Surveyor found CIM down 0.6' in good condition.