Certificate of Location of Government Corner

ID#: 610905 **Description:** SEC COR 8 9 16 17 61 **Date Set:** 9/24/1975 **County:** Olmsted

Section: 09 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of E-W fence and 1' west of N-S fence
Nail in CP SE 1.7' (leaning & rotted)
County Survey Disk in SE side blazed 24" Oak SW 27.2' (partially covered)
Spike in E side 18" Burr Oak S 24.8' (slope)
Center 18" Burr Oak E 51.4'
Post w/sign 2' south
This corner is located by GPS reference stations "Windbreaker A & B"

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 16 and 17. 80.00 chs. Set post at corner to sections. Made mound, trench, and pits planted cherry seeds S.W. and N.E.

9-1892 Thomas Fraser (P. 497 No. 469), County Surveyor, found stake with pile of stones around it avered by a Mr. Betry as true corner. Set boulder at ¼ Cor. 16-17 midway and on line.

6-1900 Robert Faser (P. 686 No. 610), County Surveyor, found a pile of stones claimed by Mr. Betry as corner. Drove new stake in center of stones. Set dry Burr Oak stake at ¼ Cor. 8-17 midway and on line.

9-24-1975 County Surveyor dug and found remains of old corner post on the north side of corner post standing. Set C.I.M. at location of old post which fit closely the recorded line and measure of ¼ Cor. 16-17 (found) and ¼ Cor. 8-17 (found).

4-6-2007 County Surveyor found CIM down 0.3' in good condition. Looked for ties and set post w/sign 2' south in E-W fence.