Certificate of Location of Government Corner

ID#: 611205 **Description:** SEC COR 11 12 13 14 61 **Date Set:** 12/12/2012 **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is at the surface.
The monument is in line with fence west.
Post with sign 2' North.
This corner is located by GPS reference stations "Klassen I & II"

Corner History:

10-1853 Gov't Notes: 80.00 chains, set post at corner and stone 24"x8"x2. B.T.'s Br. Oak 5" S24°E 67 links. Br. Oak 5" N65°E 173 links.

4-11-2000 County Surveyor visited corner location. Found nothing. Set two points for GPS traverse.

11-28-2012 County survey crew dug with hand shovels to search for original gov't stone. Dug a hole 4.5'x8'x2' deep in a northwesterly direction from the fence end post to cover the gov't proportion position. Found several stones but none matched the recorded dimensions and all were laying flat.

12-12-2012 County survey crew returned to dig for the stone with a backhoe. From the fence end post dug a hole 10' east, 11' west, 9' north and 7' south. Did not find any stones or other survey monument. Set 3.5' telspar pipe with cast iron cap at the location of the fence end post. Reset the fence end post adjacent to the telspar pipe.