Certificate of Location of Government Corner

ID#: 611304 **Description:** 1/4 SEC COR 13 24 61 **Date Set:** 9/29/2003 **County:** Olmsted

Section: 13 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 1'
The corner falls in field, 34' south of edge of field and 16' west of edge of field
Trav. Pt. "Storm III" N 97.63'
Post with sign 20' East
This corner is located by GPS reference stations "Storm III & IV"

Corner History:

10-1853 Gov't Notes: Set corner at midway 40.07-1/2, set post at quarter sec corner, deposited handful of charcoal made mound, trench and pits.

12-1894 W. Fraser (P.561 No.515 S.24) M. Wheeler, corner in open field, cultivated, took notes of John Fraser 6-1857 P.30 No.47 complete survey of section. Record shows N 1/4 24 east overrun 34 links. N 1/4 24 west short 20 links. Set temp corner on section line intersected by line from center 24 projected north from line south to S 1/4 24 the meas west proved just 20 lks short. Set no perm corner. 1/16 west set stone 19.90 M&L. 1/16 east set 1857 evidently 20.17 M&L now farm boundry not corner.

10-27-1987 Corner falls in cultivated field SE'ly of small pond built recently about 40' S of waters edge, dug 1-1/2' deep to stoney bedrock bottom found nothing dug from Tom Ferguson trav nail 1' S 3-1/2', N 2' E and 2' W to cover line projected from west and also total line which comes 2.6' N of projected 1/16 cor.

9-29-2003 County Surveyor set 1 1/2' telspar pipe w/cast iron cap down 1.2' into bedrock at double 1/16th from West stone position. Set post w/sign 20' East.

9-12-2011 County survey crew found cast iron cap in good condition.