Certificate of Location of Government Corner

ID#: 611306 **Description:** 1/4 SEC COR 13 14 61 **Date Set:** 7/31/1975 **County:** Olmsted

Section: 13 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' north of centerline of E-W twp road and in line with fence south
County Survey Disk in PP #1588 SE 67.42'
County Survey Disk in 14" Red Oak NW 60.90'
County Survey Disk in 4" Red Oak NNW 46.16'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Jones, Deputy Surveyor North between sections 13 and 14. 40.00 chs. Set quarter section post. Made trench. 7 inch Bur Oak North 3 chs.

3-1900 Robert Fraser (P. 655 No. 584½), County Surveyor, found boulder stone. Set white boulder and stake midway and on line at 1/16 south.

10-1902 William Fraser (P24B), County Surveyor, found stone. Found stone at 1/16 south.

6-25-1975 County Surveyor ran line from ¼ Cor. 14-15 (found) over Center 14 (found) and dug at William Fraser's measure but found nothing. Road cut to clay.

7-29-1975 County Surveyor found recorded white boulder at 1/16 south with pointed limestone on E. side.

7-31-1975 County Surveyor set C.I.M. over ½" x 12" rod at intersection of E-W ¼ line of Section 14 and the line from Sec. Cor. 13-14-23-24 over the 1/16 North.

12-5-1986 County Surveyor took additional ties to CIM. Spike and CSD in 14" Red Oak NW 60.90'. Spike and CSD in 4" Red Oak NNW 46.16'.

4-11-2000 County Surveyor found CIM down 0.5' in good condition.

7-15-2002 County Surveyor found CIM down 0.4' in good condition.