Certificate of Location of Government Corner

ID#: 611604 **Description:** 1/4 SEC COR 16 21 61 **Date Set:** 7/28/1975 **County:** Olmsted

Section: 16 **Township:** 107N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of E-W fence
County Survey Disk in S side 20" blazed Oak (Most southerly of triple base) W 29.83'
Post w/sign 1' north
This corner is located by GPS reference stations "PP #354 & Kirchoff"

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor West on true line between sections 16 and 21. 40.05 chs. Set post at quarter section corner. Made trench. Burr Oak 15 in. S80W 256 lks. Thomas Hunter, County Surveyor, railroad ties: 7.13 chs. from corner north to center of railroad tracks.

5-1891 Thomas Fraser (P. 447 No. 432), County Surveyor, found unmarked stake in mound and stump of bearing tree. Set stone 3"x8"x20" in place of stake.

9-1892 Thomas Fraser (P. 497 No. 469), County Surveyor, found stake and stone as recorded P. 447.

9-1911 Charles Larson (P. 164B), County Surveyor, found stone set byThomas Fraser.

11-1948 Ken McGhie, a surveyor, found 2"x8" topped limestone with hole in top.

7-28-1975 County Surveyor found stone previously found by W.H.K.S. Stone 2"x8"x21" limestone with notch cut in top center and held vertical by limestones north and south. Removed stone and set C.I.M. over ½"x12" rod. Reset stone on S. side. Corner lies in east-west fence.

8-25-2004 County Surveyor found CIM down 0.2' in good condition. Set post w/sign 1' north.