Certificate of Location of Government Corner

ID#: 611605 **Description:** SEC COR 16 17 20 21 61 **Date Set:** 7/22/1975 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5 1/2' east of fence north and 3' south of fence west
Nail in S side 15" Oak WNW 4.00'
Nail in E side 12" Oak N 2.95'
Sign in 15" Oak 2 1/2' north
This corner is located by GPS reference stations "SITM A & B"

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 20 and 21. 80.00 chs. Set post at corner to sections 16,17,20 and 21. Made mound, trench, and pits and planted cherry seeds S.W. and S.E.

9-1892 Thomas Fraser (P. 497 No. 469), County Surveyor, states corner gone. Measured from N.W. Cor. Sec. 16 to ¼ Cor. 20-21 and from ¼ Cor. 17-20 to ¼ Cor. 16-21 and set limestone as corner by double proportionate measure. Set limestone and stake midway and on line at 1/16th East. Set boulder stone midway and on line at 1/16th West.

1948 Ken McGhie, Surveyor, found limestone at 1/16th East.

7-22-1975 County Surveyor, corner comes on sidehill with only a few inches of soil over bedrock. Could fine nothing. Set 10" section of C.I.M. on bedrock by doubling line and measure from ¼ Cor. 16-21 over 1/16th West.

6-28-1995 Roger Brand and Assoc. Found C.I.M. and took ties.

8-24-2004 County Surveyor found CIM down 0.5' in good condition. Set sign in 15" oak 2 1/2' north.