Certificate of Location of Government Corner

ID#: 611704 **Description:** 1/4 SEC COR 17 20 61 **Date Set:** 4/3/2007 **County:** Olmsted

Section: 17 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' southwest of CP to fences N-E-W
County Survey Disk in S side CP NE 1.90'
Post w/sign 1 1/2' north
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor West on true line between sections 17 and 20. 40.05 chs. Set post at quarter section corner. Bur Oak 11 in. N12°E 367 lks. Bur Oak 6 in. S72°E 319 lks.

NOTE: T. Hunter railroad notes state centerline rails North 13.18 chs.

9-1892 Thomas Fraser (P. 497 No. 469), County Surveyor, states old corner post claimed as corner. Checked by bearing tree stumps and accepted. Set boulder stone midway and on line at 1/16th east.

8-4-1975 County Surveyor dug around corner post but found nothing. Doubled line and measure from Sec. Cor. 16-17-20-21 over 1/16 west (found) and set monument over 1/2"x20" rod.

4-3-2007 County Surveyor found CIM down 0.2' leaning north, took local ties and removed. Found 1/2" iron rod down 1.8' in good condition. Set 5' telspar with CIC over rod up 0.2'. CSD w/nail in S side of CP NE 1.90'. Set post w/sign 1 1/2' north.