Certificate of Location of Government Corner

ID#: 611804 **Description:** 1/4 SEC COR 18 19 61 **Date Set:** 8/4/1975 **County:** Olmsted

Section: 18 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls on SE side of CP to fences north and east
County Survey Disk in S side blazed Maple (most southerly of twins) ESE 19.3'
County Survey Disk in E side blazed 8" Maple SE 21.0'
Sign on CP 1' NW
This corner is located by GPS reference stations "Franke C & D"

Corner History:

9-1853 Gov't Notes, William A. Jones, Deputy Surveyor East on true line between sections 18 and 19. 39.75 chs. Set post at quarter section corner. Made mound, trench, and pits as per instructions.

Hunter's Railroad Notes: 15.75 chs. from corner north to center of railroad tracks.

7-1874 Thomas Hunter (P. 257 No. 257) County Surveyor, states corner post of fence declared by a Mr. Phelps as set where original quarter post stood. Found measure west to section corner within 1 link of Gov't measure. Accepted corner post as corner.

8-4-1975 County Surveyor dug around corner post and found remains of old corner post on S.E. side of corner post to fences north and east. Set ½" x 12" rod in post remains and set C.I.M. over all.

4-2-2007 County Surveyor found CIM down 0.2' in good condition.