Certificate of Location of Government Corner

ID#: 611806 **Description:** W 1/4 SEC COR 18 61 **Date Set:** 9/19/1975 **County:** Olmsted

Section: 18 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 13' west of centerline of N-S twp road
County Survey Disk in PP #2 SE 112.97'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 13 and 18. 40.00 chs. Set post and drove charred stake. Built mound. Dug trench and planted Osage Orange S.E. and apple seed N.E. Thomas Hunter's Railroad Notes: West 1/4 Cor. Section 18 11.96 chs. North from center of railroad tracks.

1890 Thomas Fraser (P. 450 No. 434), County Surveyor, could find nothing at corner.

9-1973 County Surveyor dug with backhoe covering midway and on line location but found nothing.

9-19-1975 County Surveyor set C.I.M. over 5/8" x 18" rod as corner midway and on line from West Sec. Cor. 18-19 to West Sec. Cor. 7-18.

6-17-2002 County Surveyor found CIM down 0.6' in good condition.

3-20-2007 County Surveyor found CIM down 0.8' in good condition.