Certificate of Location of Government Corner

ID#: 611905 **Description:** W SEC COR 19 30 61 **Date Set:** 9/10/1973 **County:** Olmsted

Section: 19 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in centerline of twp road north
Bottle cap in NE side PP NW 47.11'
Conc. nail in NW side PP #1708 NE 55.70'
Punch hole in top W end 15" CMP SW 36.94'
Punch hole in top E end 15" CMP SE 36.7'
This corner is located by GPS mesurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor North between sections 25 and 30. 80.00 chs. Set section corner post. Bur Oak 10 in. S20°W 174 lks. Bur Oak 6 in. S53°W 156 lks. Bur Oak 8 in. N58°W 147 lks. Bur Oak 12 in. N6°E 94 lks.

7-1874 Thomas Hunter (P. 257 Book A), County Surveyor, found stake in center of road. Set 2"x3½"x15" limestones with stake.

9-1892 Thomas Fraser (P. 497 Book A), County Surveyor, found stone in center of road.

9-10-1973 County Surveyor dug and found recorded limestone. Set C.I.M. over a 5/8"x14" iron rod all over stone.

6-8-2001 County Surveyor found CIM down 0.5' in good condition.