Certificate of Location of Government Corner

ID#: 611906 **Description:** W 1/4 SEC COR 19 61 **Date Set:** 3/29/2007 **County:** Olmsted

Section: 19 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' west of centerline of N-S twp road and 40' north of centerline of field drive east
NE Cor house foundation NW 197.05' (blocked by Pines)
Conc. nail in W side PP #1700 NNE 111.21'
T-bar 1' NE of Pine tree WSW 86.41' (leaning)
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, Deputy Surveyor North between sections 19 and 30. 40.00 chs. Set quarter section post. Made mound, trench, and drove charred stake. Planted seeds.

7-1874 Thomas Hunter (P. 257), County Surveyor, found mound in the center of the road with stone in it in line of fence running east. Also found bark and stake remains 1' down. Drove new stake, not marked, and set stone beside it.

9-10-1973 County Surveyor found 2 small limestones with definite stake hole under well below black road surface. Set 3/4"x8" reinforcing rod on bed rock below C.I.M. with small stone around rod. Corner lies .53' east of direct line between section corners.

6-11-2001 County Surveyor found CIM down 1' with broken head in good condition.

3-29-2007 County Surveyor found CIM with 2/3 of CIM broken down 1', took local ties and removed. Found 3/4" iron rod down 1.8', took local ties. Determined CIM to be leaning north from tie in PP which matched iron rod. Set 15" CIM down 0.4' over rod. Nail in PP NE 111.21'.