Certificate of Location of Government Corner

ID#: 612105 **Description:** SEC COR 20 21 28 29 61 **Date Set:** 7/1/1975 **County:** Olmsted

Section: 21 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and in centerline of twp road west
Punch hole in 18" CMP NNW 45.27'
Punch hole in 12" CMP SSW 39.52'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 29 and 30. 80.00 chs. Set section corner post. Made mound, trench, and pits and planted cherry seeds.

5-1891 Thomas Fraser (P. 447 No. 432), County Surveyor, states corner was gone, but a Mr. Leat claimed his corner post had been set 2 rods east of the original corner when standing. He had a stone planted where that post stood so used this to set point for survey.

9-1892 William Fraser (P. 497 No. 469), County Surveyor, found tree planted where corner post stood the year before so used tree to determine corner.

10-1927 E.C. Burns, Winona Co. Surveyor set a iron pipe from witness tree planted by Mr. Lietz when corner was in evidence. Witness tree 18" elm east 33'.

7-1-1975 County Surveyor dug with backhoe in "T" intersection. Found 1¼"x18" pipe 2½' deep. Set C.I.M. over pipe. Corner falls 33' west of tree used by William Fraser to set corner. The tree is now a 42" Elm. John Kerr worked in this area and Mr. Giese, a resident of the area for many years, states Mr. Kerr set the pipe here. Pipe is more likely Burns pipe.

3-21-2007 County Surveyor found CIM down 0.6' in good condition.