Certificate of Location of Government Corner

ID#: 612204 **Description:** 1/4 SEC COR 22 27 61 **Date Set:** 11/2/1979 **County:** Olmsted

Section: 22 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2' east of N-S fence, 16 1/2' south of fence east and in line with stub fence NW
County highway disk in S side wood fence post NW 2.66'
County highway disk in S side 1/2 wood fence post WNW 9.74'
County highway disk in E side wood fence post NNW 16.78'
Sign on CP 3' NW
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor West on true line between sections 22 and 27. 39.98 chs. Set post at quarter section corner. Made trench and pits and planted cherry seeds N.W. and S.E. 79.96 chs. To section corner.

4-1871 Robert Perry, Surveyor, per Thomas Hunter, Deputy, (Book A, Page 182, No. 193) found stake as ¼ post at corner of old fence. He used the corner to set the 1/16th South (19.91½ chs.) and the Center 27.

9-1889 Thomas Fraser, County Surveyor, (Book A. Page 435, No. 422) states "Found old fence post hole and part of post, and as the stake was pulled up, and it was claimed by old settlers to have stood by old post took old post as corner. Some years ago I was shown where this corner stood by H. Kimber who said he had seen the mound and stake, until breaking up The soil destroyed it. Set stone in old post hole." He used this corner to set the Center 22 at intersecting ¼ lines.

5-1895 William Fraser, County Surveyor, (Book A. P. 568, No. 520) "Could find nothing of corner as given in Survey 422, Page 435 as it had been plowed out and no one knew where it had stood as the lands had changed hands. We run a fore and back sight line from G (S.E. Cor. 22) to E (S.W. Cor. 22) and also a line from B (N. ¼ Cor. 22) over 1 (Center 22) and located corner on line B-1 and on line between G&E and planted stone for corner." Measured 39.76 chains West to Sec. Cor. 21-22-27-28 and set a stone on line and midway (20.06 chs.) at the 1/16th East.

10-12-1979 County Surveyor dug at double the line and measure from Sec. Cor. 22-23-26-27 (found) over Will Fraser's stone at the 1/16th West (found). Found a 9"x11" rectangular mark in clay with a small piece of limestone (about 6") standing at the North edge. The rectangular mark was at the S.W. side of a large round mark found at the spot pointed out by Mr. McDougall as the former corner post location.

11-2-1979 County Surveyor set a Cast Iron Cap on a square pipe (telspar) driven over a 1" sq. by 35" pipe as the corner on line from Sec. Cor. 22-23-26-27 to Sec. Cor. 21-22-27-28 and at double the measure from Sec. Cor. 22-23-26-27 over Fraser's stone at the 1/16th West. The Corner came on the South edge of the rectangular mark found 10-12-1979.

9-6-1995 Mn/Dot found CIC and took RPs. CND south side wood fence post NW 2.66'. CND south side 1/2 wood fence post WNW 9.74'. CND east side wood fence post NNW 16.78'

4-18-2007 County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition.