Certificate of Location of Government Corner

ID#: 612209 **Description:** SEC CEN 22 61 **Date Set:** 10/15/1979 **County:** Olmsted

Section: 22 **Township:** 106N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

PK nail in top of CP to fences west and SE NNE 317.16'
PK nail in top of CP to fences SW and NW NE 410.23'
County highway disk in top wood fence post NW 277.21'
This corner is located by GPS measurement

Corner History:

7-13-1886 Thomas Hunter (Book A. Page 414, No. 403 and Old Field Book 14, P. 69), County Surveyor, ran the E-W ¼ line of Section 22, setting property corners 17.49½ chs. and 18.92½ Chs. East of the W. ¼ Cor. 22.

9-12-1899 Thomas Fraser, County Surveyor, (Book A. Page 435, No. 422) set an iron rod 2½' feet long and stone as Center of Section at the intersection of the N-S ¼ line Sec. 22 and the line from the E. ¼ Cor. 22 to Hunter's stake 18.92¼ chs. East of the W. ¼ Cor. 22.

5-3-1895 William Fraser, County Surveyor, (Book A. Page 568, No. 520) found the stone set Survey No. 422 but the iron stake had been plowed out. He projected the line from the N. ¼ Cor. 22 over this corner to set the S. ¼ Cor. 22 at the intersection of this line and the line from the S.E. Cor. 22 to the S.W. Cor. 22. He also set the 1/16th East midway (20.04¼ chs.) and on line.

8-1963 John Kerr, County Surveyor, (Kerr Book 87, Page 41 and Cert. filed) "Dug in Field and found oak stake as center of section as placed by Thomas Hunter (Also W.C.F.) in 1886. Stake below plow and had small limestones set on edge around it. Placed C.I.M. with ½" steel rod below it in exact location."

10-15-1979 County Surveyor dug to verify Kerr's corner. Found a C.I.M. packed in pieces of limestone and set over a 3" to 4" long piece of pipe. Found nothing further. Electronic Traverse computations show this C.I.M. to be almost exactly on the E-W¼ line, and 1.3± East of the present N-S¼ line.

3-9-1989 Roger Brand & Associates found and used CIM.

3-9-1990 Roger Brand & Associates, Found C.I.M. down 12" in cultivated field. Took ties to monument.

9-6-1995 Mn/Dot found CIM took RP's. CND in top wood fence post NW 277.21'. PK nail in top wood fence post NE 317.13'. PK nail in top wood fence post NE 410.03'.

12-12-2000 GGG found and used monument.

6-8-2005 GGG found and used CIM.

2-23-2006 Johnson & Scofield found and used CIM.

2-15-2007 Johnson & Scofield found and used CIM.

4-18-2007 County Surveyor found CIM down 1.2' in good condition.