Certificate of Location of Government Corner

ID#: 612306 **Description:** 1/4 SEC COR 22 23 61 **Date Set:** 9/17/1975 **County:** Olmsted

Section: 23 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 200' south of centerline of CR 142 and 2' east of N-S fence
County Survey Disk in W side 10" Choke Cherry E 13.26'
County highway disk in SE side 12" Boxelder NNE 2.36'
County highway disk in N side 16" Boxelder SE 43.84'
County highway disk in E side PP SSE 48.95'
Post w/sign 2' south
This corner is located by GPS reference stations "Storm C & D"

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between 22 and 23 chs. 40.00 chs. Set post at quarter section corner Bur Oak 10" S18½ E 98 lks. Bur Oak 8" N58½E 172 lks.Thomas Hunter's Railroad Notes: Corner 6.34 chs. south of the centerline of the railroad tracks.

5-1881 Thomas Hunter (recorded by John Fraser P. 369 No. 360), County Surveyor, found old stake. Set quarry stone in place.

7-1886 T. Hunter (P. 414 No. 403) found stone set P. 369.

5-1895 William Fraser (P. 568 No. 520), County Surveyor, found stone P. 369.

7-1902 William Fraser (P. 41B) found stone.

1975 W.H.K.S. found 3"x9" topped limestone.

9-17-1975 County Surveyor found 3"x9"/16"x26" limestone (broken) found earlier in 1975 by W.H.K.S. Dug out pieces of stone and set 5/8"x26" rod. Reset stone pieces over rod and set a C.I.M. over all.

1-15-1993 Mn/Dot Found C.I.M. and took references.

3-22-2007 County Surveyor found CIM down 0.5' in good condition. Set post w/sign.