Certificate of Location of Government Corner

ID#: 612404 **Description:** 1/4 SEC COR 24 25 61 **Date Set:** 5/10/2000 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2' south of CP
Sign on CP 2' north
This corner is located by GPS reference stations "Small I & II"

Corner History:

10-1853 Gov't Notes: Set corner 40.08 midway. Set post at quarter sec. cor, B.T.'s: Burr Oak 10" S6-1/2°W 232 links = 153.12'. Burr Oak 7" N20-1/2°E 80 links, found by W.C.F. 1894 = 52.8'

6-1857 John Fraser (P.30 No.47) used corner in survey of complete section. 1/16 west 19.95 M&L, center north 39.90.

6-1881 John Fraser (P.370 No.361) found gov't stake (1/4 post). Set stone 3x8x20 or 3x6x18 south 40.63-1/2 as center 25?

12-1884 W. Fraser (P.561 No.515) found remains old post, A.P. Stearns claims he put in place gov't stake. Tested stump of NE BT, o.k. Proved corner fence post as correct corner, left as is. 1/16 west planted stone M&L 19.97.

5-10-2000 County Surveyor dug for C.P. used by J. Fraser and W. Fraser. Found post stub 18" long down 0.7' in line of fences N-S-E. Set cast iron cap on telspar pipe at post stub location.

5-10-2000 1/16th west - County Surveyor dug for W. Fraser stone. Found nothing.