Certificate of Location of Government Corner

ID#: 612405 **Description:** SEC COR 23 24 25 26 61 **Date Set:** 5/10/2000 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' south of E-W fence and 1 1/2' east of old CP
Post w/sign 2' north
This corner is located by GPS reference stations "Storm I & II"

Corner History:

10-1853 Gov't Notes: Set post at corner. B.T.'s - Burr Oak 12" S45°W 168 links, Burr Oak 10" N71°E 149 links (W.C.F. found in 1894), Burr Oak 8" S46°W 117 links, Burr Oak 9" N64°W 297 links (W.C.F. found in 1894).

6-1857 John Fellows (P.43 No.65) shows sec cor, see survey for interior breakdown of sec 26. John Fraser (P.44 No.66) shows sec cor meas west 40.25 chs. Meas north 40.00 chs.

6-1881 John Fraser (P.370 No.361) found gov't section corner. 1/16 south set limestone 3x4x20 M&L 19.98-1/2 1319.0.

12-1894 W. Fraser (P.561 No.515) found remains old stake by old fence post. Tested NW and NE B trees and stumps, marks still plain. Planted stone in place of old stake, drove new stake also. 1/16 east planted stone M&L 19.97 1318.0.

8-14-1987 County Surveyor fences E-W-N, no B trees to fit fence corner. Found 3" thick x 15" wide x 24" long limestone leaning slightly north but dug in and standing top down 6" on the side of the stone were many pieces of limestone packed around old rotted post stub which was .75' N and .25' W of the stone. Drove a board at stone location and stood stone by tree 20' ±. Stone location 2' S and 2' E of line of fence N-E-W. 1/16 east of sec cor 23-24-25-26 found fence corner to fence E-W-N, but no W.F. stones.

5-10-2000 County Surveyor found board set at stone found location in 1987. Set telspar w/CIC at board location.

4-25-2003 County Surveyor found telspar w/CIC up 0.2' and in good condition.