Certificate of Location of Government Corner

ID#: 612704 **Description:** 1/4 SEC COR 27 34 61 **Date Set:** 9/20/1995 **County:** Olmsted

Section: 27 **Township:** 106N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 2' south of centerline of CSAH 29 and 1' east of fence south
County Survey Disk in E side PP SSE 33.52'
Ref pipe S 55.40'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor West on true line between sections 27 and 34. 39.98½ chs. Set post at quarter section corner. Deposited handful flint pebbles. Made mound, trench, and pits and planted cherry seeds N.E. & S.W. 79.97 chs. To section corner.

4-1871 Robert Perry, County Surveyor, per Thomas Hunter, Deputy, (Book A. P. 182, No. 193) states that he found stake as ¼ post in center of road and in line of fence running south. He used the corner to set the Center 27 at intersecting ¼ lines

9-1943 A. Armstrong (County Highway Department Book 180, Pages 76-78) set a 2"x2" hub on line between Sec. Cor. 26-27-34-35 and Sec. Cor. 27-28-33-34 and in line with the fence South (both set in this survey). He also dug but did not find anything.

10-2 & 19-1979 County Surveyor dug for this corner with the backhoe but found only the 2"x2" hub set by Armstrong in 1943.

10-31-1979 County Surveyor set a C.I.M. over a ½" rod 2.2' South of Armstrong's hub (to hold the line of the fence South as observed in 1943 and in accordance with Perry's survey) and on line from Sec. Cor. 27-28-33-34 to Sec. Cor. 26-27-34-35 (both reset this survey--see certificates).

6-15-1995 County Surveyor referenced C.I.M. before Cold Recycling Bituminous surface on CR 29.

9-20-1995 county highway department set 1" square pipe w/cap at surface from 1995 overlay tie out.

4-11-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.