Certificate of Location of Government Corner

ID#: 612804 **Description:** 1/4 SEC COR 28 33 61 **Date Set:** 10/24/1979 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.8'
The corner falls 4½' north of centerline of CR 129
Punch hole in E end CMP SW 40.7'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor West on true line between sections 28 and 33. 40.00 chs. Set post at quarter section corner. Made mound, trench and pits, and planted cherry seeds N.W. and S.E. 80.00 chs. To section corner. Found no other records of this corner.

5-9 & 10-1977 County Surveyor dug at the 1/16th East. Found a 9"x11"x16" boulder with an old stake on the North side 2' deep. Set a ½"x12" iron in the stake hole and a 3/4"x8" iron on the East side of the stone. Doubled the line and measure from the County Highway Department C.I.M. at Sec. Cor. 27-28-33-34 over the stake at the 1/16th West and dug but did not find anything. Set a C.I.M. over a ½"x15" rod at this location as the corner.

10-24-1979 County Surveyor reset the C.I.M. set in 1977 1.93' North and 3.34' East to be at double the line and measure from Sec. Cor. 27-28-33-34 (corrected this survey-See cert. filed) over the stone found at the 1/16th west in 1977 (set a 5/8" rod over the 1/16th stone and at the road surface). Dug again here for old corner but did not find anything.

2-1-2011 County survey crew found CIM in good condition