Certificate of Location of Government Corner

ID#: 612805 **Description:** SEC COR 28 29 32 33 61 **Date Set:** 5/14/1982 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.8'
The corner falls in centerline of CR 129, 25' east of centerline of twp road south and 56' east of centerline of twp road north
PK nail in top NE'ly end of huge concrete culvert NNW 35.07'
County Survey Disk in PP #2002 NE 40.02'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 32 and 33. 80.00 chs. Set post at corner to Sections 28-29-32-33. Mound, trench, and pits as per instructions.

5-10-1977 County Surveyor set a C.I.C. on a square pipe as the corner at double the line and measure of ¼ Cor. 32-33 as set in this survey (See Cert.) over the 1/16 North (a stone found). This location makes the fence North at the 1/16 West midway to ¼ Cor. 29-32 and the fence at the 1/16 North midway to ¼ Cor. 28-29 and therefore agrees with the section subdivision around it. This corner comes in deep fill by a huge culvert over a creek so we did not dig.

9-1980 County Surveyor took references to the corner before the road is graded.

5-14-1982 County Surveyor set a Cast Iron Monument over a 5/8" smooth rod as the corner from references taken 9-1980.

2-1-2011 County survey crew found CIM in good condition.