Certificate of Location of Government Corner

ID#: 612904 **Description:** 1/4 SEC COR 29 32 61 **Date Set:** **County:** Olmsted

Section: 29 **Township:** 106N **Range:** 11W **Monument Description:** Computed Location

Reference Ties:

The corner falls 1½' north of centerline of CR 129
Rivet in top N end of CMP NE 22.38'
Rivet in top S end of CMP SE 19.38'
60d spike in 18" Pine SSE 54.41'

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor West between sections 29 and 32. 39.98 chs. Set post at quarter section corner. Burr Oak 6 in. N45°E 140 lks. Black Oak 6 in. S37°E 270 lks.

5-3-1977 County Surveyor dug with the backhoe and found a stone 18" deep over a 2½" square hole. Also found an old stake approx. ½' North. Lowered the stone and set a flattened paint can on the East side of the stone.

5-4-1977 County Surveyor set a C.I.M. over the stone.

2-7-2011 County survey crew visited the corner and could not find CIM or other survey monument. A culvert was recently installed nearby which likely destroyed the CIM.

2-22-2011 Olmsted County Survey Department computed a corner location using 1977 traverse data DWG 4-9. Field verified location with 1/16th corner set by McGhie & Betts in 1982 and with survey monument found 33' south set by McGhie & Betts in 1977. The computed coordinate values using the Olmsted County HARN 96 coordinate system are: North=142591.1834 and East=696916.2674.

5-6-2011 Joel Thoreson, County Surveyor staked the computed location of the corner. No monument set because the corner falls above a 24" CMP culvert. Verified the previous tie to a 60d spike in the west side of an 18" pine tree SSE, 54.41'.