Certificate of Location of Government Corner

ID#: 613005 **Description:** W SEC COR 30 31 61 **Date Set:** 9/20/1995 **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CR 129, 2' east of centerline of CR 136 south and 1' east of centerline of twp road north
Ref pipe NNW 72.46'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 31 and 36. 80.00 chs. Set post and drove charred stake for corner. Dug trench and built mound. Planted Osage orange SE and apple seed NE.

1965 county highway department (B. 165) found 8"x8" boulder. Set CIM over boulder.

9-26-1975 County Surveyor dug down on North side of CIM. Found boulder 1' in diameter with 8"x8" flat top 3' deep. Found dark spot in clay on North side of stone that went down below depth of bottom of boulder which was possible location of original stake. Set scrap iron around stone and reset CIM over ½"x12" rod over stone.

6-19-1995 County Surveyor found CIM. Set 1" square reference pipe w/cap on west shoulder dead end twp road 22' north of centerline 129.

9-20-1995 county highway department set 1" square pipe w/cap at surface from 1995 overlay tie out.

4-24-2009 County Surveyor found 1" square pipe w/cap at surface in good condition.