Certificate of Location of Government Corner

ID#: 613106 **Description:** W 1/4 SEC COR 31 61 **Date Set:** 10/17/1975 **County:** Olmsted

Section: 31 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of centerline of CR 136 and 6' north of centerline of twp road west
County Survey Disk in stub TP NE 32.15'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 31 and 36. 40.00 chs. Set post for quarter section corner. Bur Oak 5 in. S6½E 520 lks. Bur Oak 10 in. N85W 554 lks. Found no further records of this corner.

9-21-1973 County Surveyor no records or any knowledge or witness trees. Set transit on high place between township corner and center road near center intersection of CR 129. Town line being CR 136 centerline road at above corner came in this line or very little west. Dug entire area to 5 foot depth found road fill deep but not to clean clay. Found lone stone boulder shaped like clam shell 6x11x16 lying nearly but not compleately flat down over 4'. Nother but wood from road fill area. Created corner near stone which came in center tee road intersecting and range line as near as possible without establishing NW corner 31 Dover. Set pointed stone found vertical with 2x10x13 limestone on east side and 18" of old rotted log on S side stone, top stone down 4' ±. Corner suggested as possible until proven otherwise. No riser of any kind, no meas any direction. 36.0 NE to conc nail on NW side tele pole 958. 104.2 WNW to conc nail on N side tele pole 959.

10-7-1975 County Surveyor dug 4'x9'x5' deep to clay with backhoe but found nothing.

10-17-1975 County Surveyor set CIM over ½"x18" iron rod as corner midway and on line from SE corner Sec. 36 to East corner Sec. 25-36.

4-27-2009 County Surveyor found CIM down 1' in good condition.