Certificate of Location of Government Corner

ID#: 613306 **Description:** 1/4 SEC COR 32 33 61 **Date Set:** 2/10/2011 **County:** Olmsted

Section: 33 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 0.5'
The corner falls 9' west of centerline of N-S twp road
County Survey Disk in TP NE 96.62'
County Survey Disk in TP NW 18.15'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 32-33. 40.00 chs. Set post at quarter section corner. Deposited handful charcoal. Made mound, trench and pits and planted cherry seeds N.E. and S.W. Found no other records of this corner.

5-5-1970 County Surveyor dug with the backhoe in line with the fence at the 1/16th South, but did not find anything. Doubled the measure of this fence North and dug for the Corner in the N-S road but did not find anything.

5-6-1977 County Surveyor dug in line with the fence at the 1/16th North. Found a small boulder on top of a large boulder with its base in clay (removed).

5-10-1977 County Surveyor set a Cast Iron Cap on a square pipe as the corner on line from the location of the stone found at the 1/16th North to S. Sec. Cor. 32-33 and at 1/3 the distance. This location also made the fence West at the 1/16th South midway to S. Sec. Cor. 32-33 and the N-S fence at the 1/16th West midway to the Center 32. The North Section 32-33 was also set as part of this survey.

2-7-2011 County survey crew visited the area of the corner but did not find a survey monument

2-10-2011 County survey crew set 4' telspar pipe with cast iron cap using a computed location from the 1977 survey.