Certificate of Location of Government Corner

ID#: 613604 **Description:** S 1/4 SEC COR 36 61 **Date Set:** 9/23/1998 **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 0.4'
The corner falls 2 1/2' north of centerline of E-W twp road, 6' west of stub pasture fence north and 36' east of short pasture fence south
This corner is located by GPS reference stations "Jones & Peck"

Corner History:

1853 Gov't Notes Set post for quarter sec corner. Burr Oak 10" S30°W 12 links. White Oak 12" N59-1/2°W 60 links.

6-1880 John Fraser (P.366 No.357) board used corner to place corner west. 1/16 west set stone 2x16x20 M&L 19.95-1/2 1317.0'

4-1891 Thos Fraser (P.476 No.455) found stone and stake by side undisputed and avered to have been set in place of original gov't stake. No meas or 1/16 corners given in this survey.

5-1900 Robert Fraser (P.674 No.599) found long limestone north side road undisputed. 1/16 west found boulder stone set by John Fraser.

9-3-1975 County Surveyor dug with backhoe at John Fraser's measure from west (which also fell midway). Found road cut to clay at depth of 1-1/2' and bedrock a few inches deeper.

9-23-1998 County Surveyor set Cast Iron Cap on telspar pipe at midway and on line point between section corners.

3-5-2009 County survey crew found cast iron cap on telspar pipe down 0.4' in good condition.

2-14-2011 County survey crew found cast iron cap on square pipe in good condition.

9-1-2016 County survey crew found cast iron cap on square pipe in good condition.