Certificate of Location of Government Corner

ID#: 613606 **Description:** 1/4 SEC COR 35 36 61 **Date Set:** 9/18/1980 **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 11W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is up 0.3'
The corner falls under N-S fence
County Survey Disk in W side large twin Burr Oak NNW 16.24'
Post w/sign 1' east
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, William A. Jones, Deputy Surveyor North between sections 35 and 36. 40.00 chs. Set post at quarter section corner. Bur Oak 11 in. N75°W 347 lks. And made trench.

9-1943 Archie Armstrong (C.H.D. Book 180, Pages 76 and 77) "found fence corner with lots of hard heads around it but nothing to identify itself as a marker. I assumed fence corner to be corner." He set Sec. Cor. 25-26-35-36 midway between this fence corner and the fence corner at ¼ Cor. 24-25 and in line with the fence running South. Measured North 2634.4 to Sec. Cor. 25-26-35-36 as set.

9-18-1980 County Surveyor dug under the N-S fence and at Armstrong's measure from Sec. Cor. 25-26-35-36 (as reset this survey). A huge boulder had been pushed in here on the West side of the fence and we dug out many boulders but we could not find the base of the post described by Armstrong -- it may have stood where the large boulder is since there is already some old wire running under the boulder. Set a telspar pipe with a Cast Iron Cap as the corner under the N-S fence and at Armstrong's measure from Sec. Cor. 25-26-35-36. This loc. holds the fence West at the 1/16 South very near midway to south Sec. Cor. 35-36 and the fence East at the 1/64 North very near ¼ the distance to Sec. Cor. 25-26-35-36. We also dug at the Center 35 but found only the probable mark of a fence post which would fall appx. 3' South of the line from the E. ¼ as set and a stone over a post mark found at the W. ¼ Cor. 35 8-19-1980.

2-8-2011 County survey crew found cast iron cap on telspar pipe in good condition