Certificate of Location of Government Corner

ID#: 620104 **Description:** 1/4 SEC COR 1 12 62 **Date Set:** 9/18/1973 **County:** Olmsted

Section: 01 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of centerline of E-W twp road, 23 1/2' east of centerline of field entrance north and 3' west of fence south
County Survey Disk in N side PP #42927 ENE 79.37'
County Survey Disk in E side post NNW 34.65'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes. W.A. Jones, Deputy Surveyor. West on true line between sections 1 and 12. 39.80 chs. Set post at quarter section corner, deposited charred stake, made mound, trench, and pits. Planted cherry seeds S.W. and N.E. 79.60 chs. To section corner.

6-4-1875 Thomas Hunter, County Surveyor, (Book A Page 281 No. 278) at B (1/4 Cor. 1-12): "1/4 post missing and could not be found and as no one knew anything about it, or where it had originally stood, we measured from A (N.E. Cor. 12) to C (N.W. Cor. 12) and set a stake, not marked, midway between." He used this corner to set the Center 12 and the 1/16th
South of the Center 12.

10-30-1877 T. Hunter (Book A, Caption on Page 281) at B (1/4 Cor. 1-12): "we also set a stone 12x6x3, in center of road, and also a stone as witness 50 lks. Due north." He set the 1/16th West in this survey.

9-18-1973 County Surveyor found the recorded stone, a 3"x6"x12" limestone, with a 2"x18" wood stake on the north side. Set a 3/8" x 24" iron over the stone with a C.I.M. above. Also found part of the witness stone 33' north. .

4-13-1979 County Surveyor found the top part of the C.I.M. broken, so removed the top and first two sections and set a 10" C.I.M. over the remainder.

9-28-92 County Surveyor found CIM in good condition.

6-13-2002 County Surveyor found CIM down 0.9' in good condition.

4-5-2007 County Surveyor found CIM down 0.9' in good condition.