Certificate of Location of Government Corner

ID#: 620106 **Description:** 1/4 SEC COR 1 2 62 **Date Set:** 5/12/2009 **County:** Olmsted

Section: 01 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line with fence row west and in line with fence row south
Post w/sign 2' north
This corner is located by GPS reference stations "Wayne C & E"

Corner History:

9-1853 Set by William Jones. North on random line. 2650 Brook 5 lks wide runs east. South on tree line. 40.60 set post at gr. Section corner deposited charred stake made mound trench and pits and planted cherry seeds SW & NE.

6-1874 T. Hunter P. 247 No. 248 S3P Brockway found mound near fence corner with part of old stake in center. Measured north 40.62 to stone centerline road 2680.92. Measured south 40.10 to stone centerline road 2646.60.

11-24-1992 County Surveyor dug for stake found in 1874 by Thomas Hunter. Found large corner post base ± 1' North and 1/2' west of trav. Nail. Top of black dirt was 3' deep on south side of hole. There was too much water and black dirt to go any deeper, dug from 1/2' east to 3' west of trav. Nail and from trav. Nail north 3 1/2'.

4-5-2007 County Surveyor visited corner area and did not find anything.

5-12-2009 County Surveyor set 6' telspar pipe w/Cast Iron Cap up 0.1' at computed position from CSAH 9 R/W plats.