Certificate of Location of Government Corner

ID#: 620206 **Description:** 1/4 SEC COR 2 3 62 **Date Set:** 7/16/1976 **County:** Olmsted

Section: 02 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

Post w/sign 1' south
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes - William A. Jones, Deputy Surveyor. South on line between sections 2 and 3. 39.89 chs. Set post at quarter section corner, deposited charred stake, made mound and pits with trench. Planted Cherry seeds S.W. and N.E. 79.89 chs. To Section Corner.

6-1874 Thomas Hunter (P. 247 No. 248), County Surveyor, states corner gone. Dug extensively and carefully but found no evidence of the corner. Set a temporary stake at proportionate Gov't measure.

7-14-1976 County Surveyor dug around the corner post to fences N-S-E-W. Found a 4" x 5" / 8" x 18" limestone down 18" on the East side of the corner post to fence N-S-E-W. Also found the remains of an old stake or post on the North side of the stone 30" deep

7-16-1976 County Surveyor set a C.I.M. over a 1/2" x 2' rod as the corner on the section line and at the prorated Gov't measure by electronic traverse computation. The corner is .13' West and 2.83' North of the stone found.

11-19-92 County Surveyor found CIM in good condition. P.P and post used as ties in 1976 are now gone. Set survey sign on post 1' South of CIM.)

4-5-2007 County Surveyor found CIM down 0.3' in good condition.