Certificate of Location of Government Corner

ID#: 620405 **Description:** SEC COR 4 5 8 9 62 **Date Set:** 8/3/1973 **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 6' south of centerline of E-W twp road
Natural bark seam between trunks of twin 14" & 18" Burr Oak NNE 84.0'
County Survey Disk in PP NE 45.90'
County Survey Disk in PP SE 39.02'
Concrete nail in PP SW 40.15'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes North between sections 8 and 9. 80.00 chs. Set section corner post. Deposited handful of charcoal. Made mound, trench and pits. Planted cherry seeds NE and SW.

5-1903 Charles Armstrong (P. 46 Book B), County Surveyor, states corner gone. Set stone 6" x 14" x 16" by measurement.

8-3-1973 County Surveyor found recorded 6" x 14" x 16" limestone 2.6' deep. Drove irons on east and west sides of stone and set CIM over all.

8-27-1973 County Surveyor dug and found some evidence enough to create corners at 1/4 5-8 and 1/4 4-9. At 1/4 4-9 found small piece wood stake on exact 26.4' line South of section corners 2' west of fence S. At 1/4 5-8 found dug area in proper place 4' west of fence north which could easily be site of original corner. Measured west to 1/4 5-8. 2638.3'; Measured east to 1/4 4-9 2635.1'; Measured 1/4 4-9 east to 3-4-9-10 2633.3'.

5-15-1997 County Surveyor found CIM down 0.8' in good condition.

6-12-2001 County Surveyor found CIM down 0.6' in good condition.

4-20-2009 County Surveyor found CIM down 0.8' in good condition.