Certificate of Location of Government Corner

ID#: 620409 **Description:** SEC CEN 4 62 **Date Set:** **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-1903 C. Armstrong P 46 B set oak stake at interestection right lines 36" willow S 12°E 34 or 39 links. Set oak prop corner stakes for lines south. East 8.21 then 11.71 to 1/16 corner then 19.92 to E 1/4. West 6.20 then 9.98 then 23.71 to 1/4 cor.

4-26-71 County Surveyor set temp mark as 00 for 1/4 4-5 in line fence west which came 37.0 west of staple in barb wire in corner post. East some 3' above ground. Measure line east carefully found positive fence line south A 1567.7. Found positive fence line south A 2226.7. Found fence line north (spooled wood stake set in 6-1970 to help find N 1/4 at 2644.0. Pulled spooled stake, drove down to 3" up in line main fence west at 26.37° from centerline road west. At center drove 12" oak machined spool from old furniture piece up 2" with glass (blue) broken around it as center by line fence West and measured from west at 2637 and leaning huge willow in place in 5-1903. Nail in top leaning willow SE 23.0; blazed 10" soft maple in Fe L nails NE 11.0; ??? Line fence north E7.0. Actual meas N 4.0' for main line due west.