Certificate of Location of Government Corner

ID#: 620504 **Description:** 1/4 SEC COR 5 8 62 **Date Set:** 8/27/1973 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2 1/2' north of centerline of E-W twp road and in line with fence north
Concrete nail in W side CP N 25.53'
Concrete nail in PP #15913 SE 43.13'
Center of a pump standard at S point level SW 87.7'
Bottle cap in TP WNW 118.2'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes West between sections 5 and 8 40.00 chs. Set quarter section post. Made mound, trench, and pits. Planted cherry seeds N.E. and S.W.

5-1877 Thomas Hunter (P. 310 No. 304), County Surveyor, states corner missing, but fence line claimed set on line when 1/4 post was standing.

5-1903 Charles Armstrong (P. 46 Book B), County Surveyor, used line of property fence running north to measure east to set Sec. Cor. 4-5-8-9.

8-27-73 County Surveyor dug entire area 8' square from 5' east to 5' west of fence North - found indications of corner search in NW side of excavation and one spot dug deep into clay like wood stake or some definite corner in that area. Accepted center dug area as corner altho 4' west of fence north which by eye has definite westward turn further norther as fence runs into brush and trees. Set CIM over iron, wood stake piece and trash.

5-15-1997 County Surveyor found CIM down 0.8' in good condition.

7-30-2001 County Surveyor found CIM down 0.7' in good condition.