Certificate of Location of Government Corner

ID#: 620506 **Description:** 1/4 SEC COR 5 6 62 **Date Set:** 7/31/1981 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' east of centerline of CR 102 and 2' north of fences east and west
Conc nail in N side PP #15966 WNW 32.65'
Bottle cap in S side fence post E 27.81'
This corner is located by GPS measurement

Corner History:

Set by William Jones 9-1853. S.20'E on true line between 5 & 6. 40.12 Set post at gr. Sec corner deposited charcoal made mound of earth and sod, trench and pits, and planted cherry seeds NE & SW.

5-1871 T. Hunter P 184 No 195 found stake in center road, even with surface. 1/16 North set stake at 19.95 1/2 then 20.05 1/2 to Sec. Cor this 1/2 mile 11 lks short govt meas; to west set stake M & L 20.05

8-23-1973 County Surveyor dug with backhoe from center road. West in line fence east. Road and building site 600 ± North shows road may have been moved east. Land and road level and normal grade found 10" of very old stake with only bark on one side of stake left, took pictures, set 1/2 x 20" pipe with 2 pepsi bottles unbroken on N & S side pipe and CIM over pipe down 4" 25.95' NWly to concrete nail NE side PP 15966.; 35.55 1' S of E to concrete nail S side corner post. Made from old utility pole (many spike holes); 215.0' NNNW to SE corner large Quonset shed

7-31-1981 1/16 North: County Surveyor dug from a point on line from N 5-6 to 1/4 Cor 5-6 and in line with fences East and West (which came in Wly wheel track) West for 2'+ and East to 1' E Centerline where we found the remains of an old stake 3' deep driven well down into clay and very tappered. Drove 5/8" rod in stake hole.

7-31-1981 County Surveyor dug on line N 5-6 over stake found at the 1/16 South. Immediately struck stone by 2" thick down 1' and wood pieces all around. Found stake hole .4' East of the center of the stone. Dug stone down and set iron on North and South sides. Set a CIM centered over stake mark. Corner 3' East centerline and 2' North of fences E and West. RP's concrete nail in N side PP #15966 WNW 32.65' pop can in S side fence post East 27.81'. Left old CIM in place for the time since it is a control point in this survey.

8-4-1981 1/16 West County Surveyor dug and found remaining 5" of Hunter's stake 18" deep and 5 1/2'North of the E-W fence. Put short bolt and spike and remaining wood pieces down 2' at stake location. Corner N E-W fence.

7-8-1982 County Surveyor dug out CIM set 8-23-1973 but left pipe below in place to hold location of stake found.

7-30-2001 County Surveyor found CIM down 0.4' in good condition.