Certificate of Location of Government Corner

ID#: 620604 **Description:** 1/4 SEC COR 6 7 62 **Date Set:** 6/16/87 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of centerline of E-W twp road and 2' east of fence north
This corner is located by GPS measurement

Corner History:

Set by William Jones 9-1853. East on tru line. 38.53 Set post at gr. Sec. Corner deposited handful of charcoal made mound trench and pits, planted cherry seeds N.S.E. & W.

5-1871 T. Hunter P. 184 No. 195 found stake standing in mound with pits plain. 1/16 West set temp stake for lien North on line and 19.96 then 18.49 to sec. Stone. 38.45 total. 8 linkns short of recorded Gov't measurement.

5-1883 T. Hunter P. 382 No. 373 Road in grade, corner gone used old fence line north. Measure west to sec. Stone 38.45 P.184.

8-24-1973 County Surveyor dug entire road corner gone. Dug in line fence North and 5' weide in center road. No corner recorded and if there was it wouldn't have been there unless 4' long to start with. Clay down 24" to 30" and road and staples and old glass insulator right on clay. Land slight slope up toward east but don't believe road traffic destroyed rod bed that much as there was no road in 5-1871. Corner completely lost no section corner east, also lost, 1/16 fence west surveyed now non-existant, running North in 5-1871.

8-10-1981 County Surveyor dug from our traverse nail set in the center of the E-W road and in line with the fence north. (This was also the S1/4 edge of the previous 1973 diggings) 4' + East, 4'+West, and 9'South by 2 1/2' deep to clay. The old road here was right on clay. We did not find anything. We were digging to cover the line of the fence North, line from the N1/4 Cor 6 over the stone found at the Center 6, and also double the measure from the Center 6 over the fence West at the 1/16 South. 1/16 West: Dug from a point 3' West of the traverse nail set in the center of the E-W road and in line with possible old fence ridge running North for 8' West and 7 1/2' South by 3 1/2' to clay. Conditions were good but found nothing. We were digging to cover Hunter's measure (and also 2' overrun (1/4 mile) from both the fence line North at 1/4 Cor 6-7 and also the line from n 1/4 Cor 6 over the stone found at the Center 6. Centered over line from the CIM at SW 6 and the center of the road at 1/4 Cor 6-7 (line fell approximatly 3' South of the nail here). Dug Southerly to allow for either SW6 or 1/4 Cor 6-7 being further South.

6-16-1987 County Surveyor set C.I.M. over 1/2" pipe. Corner 4' South of Centerline E-W road and 2' East of fence running North. Set by on line N 1/4 corner over center stone fd and double calc. Center over fence at 1/16 South.

7-30-2001 County Surveyor found CIM down 0.2' in good condition.