Certificate of Location of Government Corner

ID#: 620605 **Description:** W SEC COR 6 7 62 **Date Set:** 6/16/87 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3 1/2' north of centerline of E-W twp road and 9' west of fence south
County Survey Disk in PP #43340 S 32.24'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Ball Deputy Surveyor. North between sections 7 and 12. 80.00 chs. Set post and built mound with trench. Planted osage orange S.E. and apple N.E.

5-1871 Thomas Hunter (P. 184 No. 195) County Surveyor, found stone in the center of the road.

5-1883 Hunter (P. 382 No. 373) found stone P. 184. Measured east to fence line north and south to railroad tracks.

12-1910 Charles Larsen (. 142B), County Surveyor, found boulder corner.

5-1964 John Kerr (B. 89 P. 29) County Surveyor, measured north Hunter's measure from the center of the railroad tracks but found nothing. Set C.I.M. over 1/2" rod. Measured east to fence north.

11-30-1970 County Surveyor dug in road and found a small boulder. Set 5/8" x 2' rod.

8-27-1973 County Surveyor set CIM directly on stone. Removed Kerr's CIM. Correct corner is 6.7' north and .9' east of Kerr's CIM location.

7-7-1982 County Surveyor dug north of CIM found a pointed boulder with a 7"x11" base x 15" long standing and dug well into clay.

6-16-1987 County Surveyor set CIM over 3/4" re-rod at location of stone found 7-7-82. Removed CIM set in 1973.

9-22-2006 County Surveyor found CIM down 0.6' in good condition.