# Certificate of Location of Government Corner

**ID#:** 620606 **Description:** W 1/4 SEC COR 6 62 **Date Set:** 6/12/87 **County:** Olmsted

**Section:** 06 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls in line with fence north and 1' south of E-W fence
Sign on CP 1' north
This corner is located by GPS measurement

**Corner History:**

Gov't Notes 1853. Oct. Ball, Deputy Surveyor. North between 1 and 6. 40.00 Set post and drove charred stake.

5-1871 T. Hunter P. 184 No. 195 found stake in original mound plain. 1/16 North set stake M & L 19.95 (1316.7 N25'W. Stakes M & L on other lines north were property measurements but not on west line couldn't figure out why. 1/16 east set stake on line E1/4 6 and prop. Meas. 18.23 then 19.94 to center sec. 6.

11-4-70 County Surveyor measured from township corner south set small nail at 1316.7 which came just south (30') of dry wash draw in pasture. Quite deep soil but could not find stake. Continued to E-W fence at 1/4 line at 2634.7 at corner posts. 2 new posts one for new fence west, one for new fence north. Dug over 2' in all directions from both corner posts found an ancient corner post with just shell remaining set with channel steel post in cluster old post with 1" x 2' rod on channel. 2' to clay. Measure from CIM set 1964 at SE corner section 1 to post. From ?? Corner 2636.0 record 2633.4 (1871). With SE 1 moved 6.7' north to stone found measure is 2644.6. Middle of road at SE 1 would make it 2640 even. Farmers in area declare centerline road never changed. Behind old post exact spot of original stake in original mount. County Surveyor from field book. Cor lies 3' East of Corner fence post. From West and 2' East of main fence line going North. Corner lies about 1' South of E-W fence lines.

7-10-1981 County Surveyor found 1" iron set by Roger in 1970. 1' South of E-W fence and 2' East of the main line of the fence North.

7-30-1981 County Surveyor dug from a point at Hunter's measure from NWS 6 and under N-S fence 4 1/2' East, 3' South, 1' North, and 2' West by 3' to clay. Found nothing.

8-6-1981 County Surveyor dug from 1/2' west of the t.n. near W. 1/4 Cor 6, West for 7'm, North 2 1/2', South 2 1/2' by 2' deep to clay. Found the remaining 12" of an old stake (top down 16") 1.25' West and .5' North of the traverse nail. Removed stake to office and set a flat iron to hold location.

6-15-1982 County Surveyor dug some more off the West side of the hole dug last year. We have now dug up to 4 1/4. West of the N-S fence. Found nothing further.

6-12-1987 County Surveyor removed flat iron set at stake location found 8/6/81 set CIC/P ? Removed 1" shaft set by Roger Brand in (1970) corner 8.3' W of C.P. to fence E-W-N and .7' So of fence west by corner in line fence running west in line fence far north.

10-19-2006 County Surveyor found cast iron cap on telspar pipe at surface in good condition.