Certificate of Location of Government Corner

ID#: 620704 **Description:** 1/4 SEC COR 7 18 62 **Date Set:** **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 12W **Monument Description:** The corner falls in Chester Woods Lake

Reference Ties:

Contact County Surveyor for corner position

Corner History:

9-1853 Set by William Jones. West on random line. 42.20 Brook 10 lks wide runs south; 77.55 Brook 4 lks wide runs South. East on true line. 38.56 Set post at gr. Sec. corner. Red Oak 5 N 27 E 20; Red Oak 10 S 26 W 10.

6-1893 W. Fraser P512 No. 480 S 18 J. Willson, J. Campbell found stake set P. 382. Left as found - no measure.

10-1930 J. Kerr B. 4 P. 10. Corner gone. Set stone 3 x 3/8 x 28 on line (Stake on S. side). Measure east to NE 18 2628.2; Measure West to NW 18 2526.8'. Burr oak N 11° 20 W 27.0; 12" burr oak S 56° 30W 60.6'; 10" burr oak S 6° E 76.6'. Govt. N line 18 78.56' - 5185.0; J. Kerr 5155.0'.

8-24-1981 1/16 North: County Surveyor dug from t.n. set on the North side of the corner post to fences West and South for 2 1/2' North, 3' South, 2' East, and 1 1/2' West by 2 1/2 deep to clay. Found the base of a post with cement poured around it 1.5' East of the nail. Found the remains of a small post 2.1' South and .6' West of the tin. This was the oldest post in the area. Found nothing further.

8-24-1981 County Surveyor dug from a point 3' West of Kerr's stone as follows: 3' NNE; W5'. Found wire running west from the stone for 8' to 9' (it may have continued West if we had dug farther). The area appears to be in a slight cut of the old road running East and NW. The soil was all sand and easy digging. We did find a drag tooth lying down and down 1' approximate 5' So and 8' West of the stone. Drove a lath here with stone around it to hold location since we had no instruments to determine more accurately. We were digging to cover Hunter's measure from the 1/16 fence North and line from the fence North at 1/4 corner 6-7 over the fence corner at the 1/16 N (of 1/4 corner 7 - 18) and also 1/4 line across Sec. 18 (line from cale S1/4 corner 18 over the fence at 1/16 N and post found at Center 18.

7-26-1982 County Surveyor chained 1310. East from Kerr's stone to the fence running South at the 1/16 E. Kerr's stone is in line with the fence farther E on the North side of the old road running East. We chained 139 1/2 West from Kerr's stone to the E bank of creek (East bank not nearly as definite as W bank here). Set nail 15.16' E of Kerr's stone and on Sec line.

9-1-1982 County Surveyor dug from Kerr's stone, South for 6' and East for 15'. Did not find anything. Digging to cover Hunter's measure from the E-W 1/4 line Sec. 7 (using 2640 South of the stone found at NW 7 as N-S for W 1/4 &). Hunter's full measure would come approximately 5' South of Kerr. Also to cover a Will Fraser Center 18 which could have been East of Kerr's on comparing measure to the W 1/4 corner 18.

4-13-2009 County Surveyor visited area of corner. The corner now falls in Chester Woods Lake ± 20' westerly of east shore.