Certificate of Location of Government Corner

ID#: 620705 **Description:** W SEC COR 7 18 62 **Date Set:** 10/12/1963 **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 18' east of centerline of Chester Woods access road
Spike in small Oak NW 6.38'
Spike in small Oak SW 6.13'
Post w/sign 1' east
This corner is located by GPS reference stations "Screamer A & B"

Corner History:

(from cards) Gov't Notes 1853 Oct. Ball, Deputy Surveyor. North between 13 and 18. 80.00 Set corner post Br. Oak 10 in S88W 19 lks. Br. Oak 14 in. N38W 176 lks; Br. Oak 10 in. S10E 54 lks. Br. Oak 12 in. N75E 144 lks.

12-1910 Chas. Larson P.142 B S. 12. Found no corner - ground frozen. Set stone. Everlything 40 chs. Found very little, poor survey.

10-1930 J. Kerr B 4 P 10. Corner gone. Set stone 2 x 18 x 30. Cedar stake W side. Run line to W 1/4 6 to help set corner for E-W (line) Center 14 " burr oak S 24° 12.8; 40d spike 14" borr oak N 20°E 25.5'. Actual data for placing corner, measure W 1/4 18 North to centerline RR 6257.2 + record of 1632.18' (Hunter record from centerline RR N to W 6-7) 7889.38' 1/3 of which 2629.8' and continued to line to corner post at W 1/4 6 for range line. Too late to adjust corner now but W 6-7 at least 1640 or more from centerline rr N. All 4 side of corner common land for 1/2 mile so changing corner of no significance at all

10-12-1963 found west section corner of Corner Sections 7 and 18 wich was evidenced by limestone. Aslo set permanent marker of a Cast Iron Monument

4-13-1981 County Surveyor found CIM in circle of limestone in brush N-S true line. Kerr's 1930 witness trees still in place.

8-30-1982 County Surveyor dug from a point 3' South and 1' West of Kerr's CIM, South for 6' and West for 3'. Found possible stake hole down 14", hole 3" diameter and ran down 8". Mark not pointed but ground very hard and bedrock 3" below. RP's to mark - spike in small oak NW 6.38'; spike in small oak SW 6.13'. The mark approximately 7.2' South and 2.2 west (d=7.74) Had nothing to determine direction. Measured 117' to 120' South from Kerr's CIM to the fence West (very crooked tree to tree) which Hunter recorded 1.70 ch. South. We chained South (very roughly) approximately 1314 and found small limestone standing under N-S fence.

7-27-2001 County Surveyor found CIM down 0.2' in good condition.

9-26-2006 County Surveyor found CIM down 0.2' in good condition.