Certificate of Location of Government Corner

ID#: 620706 **Description:** W 1/4 SEC COR 7 62 **Date Set:** 11/9/64 **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

West 1/4 7 Eyota 106-12; East 1/4 12 Marion 106-13. Gov't Notes 1853 Oct. Ball, Deputy Surveyor. North between 7 and 12. 40.00 Set post and drove stake.

5-1883 T. Hunter P. 382 No. 373. Morse, etal. Corner missing. No evidence or knowledge of corner. Set temporary point 40 chs south of NW Cor. 7. 16 couth set stake 20 chs south of above measure.

12-1910 Chas. Larson: P. 142 B found nothing as corner. Set temporary point for line west at 40 chs from NW 7 as Hunter did P. 382. Set Center section 12 a limestone and found W 1/4 12.

10-1930 J. Kerr B. 4 P. 10 thru 17 A. Did not set or search for corner but measureed from W 1/4 18 to center railroad tracks to determine where to set NW or 18. 2629.8' for each 1/2 mile.

5-27-64 J. Kerr B. 89 P. 29. Measured from centerline rails North 1632' and from property lines running S 12 north on S line W 1/2 sec 6 106-12. 1220.34' and 1317.36' dug and found small stones and wire. Set NE 12 at that point 2537.7'. B. 89 P. 70 ran line from SE 12 as set 1930 North to CIM set above 5258.08'

11-9-1964 J. Kerr running section line and placing corner at proportionate distances according to previous record. Set CIM.

7-6-1982 County Surveyor dug with backhoe on the North side of Kerr's CIM as follows: 15' N, 4' E, 9'W 5' NNW. Found only one possible stake mark with referencing approximately 11 1/2' North and 4 1/2' West of the CIM but not definite at all.

7-6-1982 1/16 South: County Surveyor dug with backhoe as follows: 4'N, 3" NNE, 4 1/2' SSE; and 8' S. Found nothing but a post mark 1.3' North and .4' East of the t.n.

5-30-1997 County Surveyor found CIM down 0.6' in good condition.

5-7-2001 County surveyor found CIM down 0.6' in good condition.