Certificate of Location of Government Corner

ID#: 621009 **Description:** SEC CEN 10 62 **Date Set:** 7/16/2015 **County:** Olmsted

Section: 10 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

3" Mag spike and washer

Reference Ties:

The monument is at the surface
S 51°12'28" E 198.62' to a Pin and Cap stamped "B15" (per Plat-55-113)
S 22°51'07" W 190.20' to a 2" square pipe & cap "B8" (per Plat 55-112)
N 53°13'03" W 94.97' to a nail and disc in the southeast face of a power pole, up 6'
This corner is located by GPS reference stations "Pries & High Plains"

Corner History:

10-28-1872 Thomas Hunter Book A P.209. Set marked stake at intersecting 1/4 lines and took two BTs. 8" burr oak S 57°E 192 lks 5" burr oak South 135 lks. Set stone at 1/16 corner East
(from cards: 1/16 East set stone M & L 20.05 S 89° 55' E; 1/16 south drove stake M & L 20.02 N 5° W.)

6-19-1893 W.C. Fraser Book A P.511 Found stake set in P.209 and checked BTs. 1/16 corner east found stake in stones, set new stone 7"x7"x15" in place of stake.

9-1966 John Kerr Kerr Book 94 P.53. Found 1/16 corner stone East in an island around large Oak tree. Found 1/16 stone east of center 10 in island around large oak tree as P. 511. Measure South 2645.1' which checks very close; center large oak tree in island. SW 7.6; 3" metal standard US 14 RW marker with new type marker along side WSW 1.25'; centerline pavement South on 1/16 line 149.1' (assumed to be 1/16 line or very near).

5-1972 County Surveyor after resetting all Quarter corners, ran intersecting lines to set mark at Center of Section 10. Also found 1/16 corner stone East which was used to set East 1/4 corner.

5-11-1972 County Surveyor set temporary mark in concrete as corner by intersection 1/14 corner lines direct. All 1/4 corners set by actual pro-rated record measure and line. Measure West 2604.8'; east M & L 1323.08; Mark 2.58' E of centerline Hwy 42, 35.08' N of centerline hwy 14.

4-30-1974 MHD crew set brass plug at center of section 10.

7-30-1995 Yaggy Colby used computed center at intersecting quarter lines.

7-17-2001 McGhie & Betts found and used drill hole in concrete at center of section 10.

1-3-2002 GGG found and used drill hole in concrete at center of section 10.

7-18-2002 County Survey Crew found drill hole and measured its position using GPS.

2-3-2006 Pape Land Surveying used computed center for Stone Ridge Plaza.

5-19-2014 MnDOT Survey Crew set Nail & Disc at computed center of section. Set 3 new ties: Pin at NE Corner of wood retaining wall – S 16°26’ W 179.68’; Nail and Disc in PP - S 36°34’ E 125.90’; MnDOT 3D Monument “5506-A” - N 82°33’ W 86.82’.

7-18-2014 MnDOT Survey Crew checked for and did not recover previous county highway disk ties.

7-6-2015 The existing monument was destroyed by the construction of a highway roundabout intersection. MNDOT reset a 3" Mag spike and washer. MNDOT set ties and provided the information to Olmsted County.
S 51°12'28" E 198.62' to a Pin and Cap stamped "B15" (per Plat-55-113)
S 22°51'07" W 190.20' to a 2" square pipe & cap "B8" (per Plat 55-112)
N 53°13'03" W 94.97' to a nail and disc in the southeast face of a power pole, up 6'

8-14-2018 County Survey Crew found mag spike with washer at surface in good conidition.