Certificate of Location of Government Corner

ID#: 621204 **Description:** 1/4 SEC COR 12 13 62 **Date Set:** 4/23/1979 **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' west of fence south and 6' south of centerline of E-W twp road
County Survey Disk in W side brace post SW 40.92'
PK nail in W side fence post SSE 55.0'
County Survey Disk in S side PP #20 (up5') ENE 119.98'
County Survey Disk in E side brace post SE 43.68'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor. West on true line between sections 12 and 13. 40.18 1/2 chs. Set post at quarter section corner. Deposited charred stake. Made mound, trench and pits and planted Bur Oak acorns S.W. and N.E. Cherry seeds S.E. and N.W. 80.37 chs. to section corner.

6-1875 Thomas Hunter, County Surveyor, (Book A Page 281 No. 278) found the remains of the old stake in the center of the road. Set a boulder stone 5" x 11" x 19" in its place. Measured 39.84 chs. West to Sec. Cor. 11-12-13-14. Set a stake at the 1/16th North midway (20.08 1/4 chs.) and on line to the Center 12 which he set at intersecting 1/4 lines.

8-2-1973 County Surveyor dug out the entire surface of the road with the backhoe but did not find anything.

9-25-1975 County Surveyor dug again but did not find anything.
Will set corner by MSMT E & W and from fence @ Cen. 12

4-19-1979 County Surveyor dug at the 1/16th North and found a stake hole down about 20" from the surface and 2' West of the corner post to fences N-E-W. Also dug at the Center 12 (a 3 corner post complex). Did not find anything; however, the base of the fence corner post of the fence South would be within a few inches of the intersection of the E-W 1/4 line with the line from the North 1/4 Cor. 12 to the stake hole found at the 1/16th South of the Center 12.

4-23-1979 County Surveyor set a C.I.M. over a 1/2" x 3' rod on line from the North 1/4 Cor. 12 (found 1973) over the stake hole found at the 1/16th South of the Center 12 and at double the measure (1325.62) from the Center 12 (calc. at the intersection of the E-W 1/4 line and the line from the North 1/4 Cor. 12 to the stake hole found at the 1/16th South of the Center) over the stake hole found at the 1/16th South. Measured 2629.27' West to the S.W. Cor. 12.

6-17-2002 County Surveyor found CIM down 0.4' in good condition.

3-20-2007 County Surveyor found CIM down 0.4' in good condition.